



- Integrated Point of Sale Dock for the Apple iPad®
- Modern style
- 3 Year Manufacturer Warranty



Elo PayPoint® for the Apple iPad®

All-in-one, Elo PayPoint for the Apple iPad integrates cash drawer, barcode scanner, receipt printer, and customer facing display, for your favorite Apple iOS point-of-sale (POS) software application.

The flip-for-signature docking tray for the Apple iPad encourages shopper engagement and electronic receipt delivery. Retail peripheral expansion is available through an additional serial port. iPad charging supported when docked.



PRODUCT OVERVIEW

What You Can Do:

- Deploy your favorite POS software on a stylish all-in-one platform that works as good as it looks
- Capable of supporting additional peripherals
- Stay connected wirelessly through the connected iPad

What's Included:

- Docking tray that accepts Apple iPad 4, iPad Air, or iPad Air 2
- Integrated Cash Drawer
- Barcode Scanner
- Receipt Printer
- Customer Facing Display

Why It's Better:

- All-in-one, everything you need
- Modern style
- Professional product built to last
- 3-year Manufacturer warranty



Elo PayPoint® for the Apple iPad®

Specifications	
Color	White
Apple iPad Support	iPad 4, iPad Air, iPad Air 2
Apple iPad Charging	2.5A with overcurrent protection via Lightning® connector
PayPoint Dock Integration	iOS SDK for POS software interface to hardware peripherals inclusive of diagnostic application and source code
Flip-for-Signature	Docking tray tilts -40 to +45 degrees
Connectivity	Wi-Fi, Bluetooth or 3G/4G LTE via Apple iPad
Serial Ports	1 x native serial port (RJ-45)
USB Ports	1 for accessory charging only (1A 5W)
Cash Drawer	4 bill trays, 5 coin compartments, 1 check slot, mechanical locking key
Printer	Thermal 2 1/4" (58mm); accepts 2-inch (50mm) thermal paper roll
Bar Code Reader	1D Scanner
Customer Facing Display	2 line, 16 character display
Dimensions	13.5" x 15.7" (343mm x 399mm)
Weight	12.75 lbs (5.8 kg) unpackaged; 16.5 lbs (7.5 kg) packaged
Shipping Box Dimensions	18.97" x 13.85" x 17.40" (482mm x 352mm x 442mm)
Temperature	Operating: 32°F to 95°F (0°C to 35°C); Storage -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%
Manufacturer Warranty	3 years
MTBF	50,000 hours demonstrated
Power Supply	Internal AC input voltage: 100-240VAC; Input frequency: 50-60Hz; 30W max.



Call us today
1-844-296-7828



* This is a third party Web site. Elavon is not responsible for the content of, or products and services provided by Elo Touch Solutions, nor does it guarantee the system availability or accuracy of information contained in the site. This Web site is not controlled by Elavon. Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2015 Elo Touch Solutions, Inc. All rights reserved. DS000108, rev B 07/15 © 2016 Elavon, Inc. All rights reserved. Elavon is a trademark in the United States and other countries. All features and specifications are subject to change without notice.

Elavon **elo** TOUCH SOLUTIONS

© 2015 Elo Touch Solutions, Inc. All rights reserved.